

Jet / Pressure Wash

Autowash Engineering supplies a variety of pressure washing equipment ranging from small industrial cold water mobile machines to high specification static site steam cleaning cabinets.



Please contact us with your requirements and we will offer a machine to suit your application.

Standard features:

- Low revving brass pump
- Sturdy stove enamelled steel cabinet
- Large water break tank
- Steam stage
- Room for chemical/fuel storage in cabinet
- High pressure chemical application
- Adjustable time out when not in use
- Safety voltage at control panel

Optional features:

- Stainless steel cabinet

- Flame failure control
- Remote control
- Timed chemical operation
- Flue system
- Token/coin operation
- Frost protected hose reel cabine

Technical specifications:

Model

400 SH

240v

400 SH

110v

400 SH

415v

400 SH

415 HP

Max working

pressure

100bar

(1450 psi)

100bar

(1450 psi)

150bar

(2175psi)

200bar

(3000psi)

Max water flow

rate

12

litres/min

12

litres/min

15

litres/min

15

litres/min

Max temp

(stream)

90°C

(150°C)

90°C

(150°C)

90°C

(150°C)

90°C

(150°C)

Motor

3hp 2.2kW

240v

3hp 2.2kW

110v

5.5hp 4kW

415v

7.5hp 5.5kw

415v

Pump type

Brass with 3 ceramic pistons, stainless steel valves and fibre seals
Electrical cable

9m

9m

9m

9m

Construction
Dimension (in mm)
Weight

Stove enamelled steel or stainless steel (optional extra)
D600 x W850 x H1750

250kg

250kg

250kg

250kg

Operating system	Low pressure bypass with adjustable time out when not in use
Std feature	Frost protection, 24v safety control voltage & high pressure chemical